

'ULTRACLEAN' BENCH-TOP ULTRASONIC TANKS

STANDARD FEATURES:

- **Stainless Steel Construction.**
- **Sizes from 4 to 80 litres.**
- **Digital Temperature Control.**
- **Digital Process Timer.**
- **Low Liquid Level Protection.**
- **Manual Drain Valve.**
- **Drop-In Lid**
- **Mesh Component Basket.**
- **2 Years' Warranty.**



Ultrasonic cleaning, utilising high-frequency sound waves to create mechanical agitation within the cleaning medium, has long been accepted as a highly effective method of component cleaning. The process produces a deep cleaning action without stress or damage to components.

Our range of 'Ultraclean' bench-top tanks brings the power of ultrasonic cleaning in a convenient, portable format. 'Ultraclean' bench-top tanks are designed for use with water and biodegradable detergents. Manufactured entirely from stainless steel, they are completely self-contained and offer digital temperature control and process timing as well as a manual drain valve and essential safety features such as low-liquid level protection. The tanks can be used anywhere on a stable, level surface (such as a bench or work-top) and only require a 240V supply.



D&S Ultra-Clean Ltd

6 Berkeley Court, Manor Park, Runcorn, Cheshire WA7 1TQ

Tel: +44 1928 580460

E-Mail: sales@ds-ultra.com

www.ds-ultra.com

EQUIPMENT SPECIFICATION

'Ultraclean' tanks are ideally suited to development projects, or small-scale, production cleaning of a wide variety of items including: jewellery, optics, dental equipment etc. They are designed for use with solutions of biodegradable detergent and water and are available in a range of sizes from 4 to 80 litres capacity. Larger models (40 litres capacity upwards) can also be supplied with useful options such as heated rinse stage and oil separator. All models carry a comprehensive, 2 years' warranty.

DIMENSIONS (l x w x h)			
MODEL	OVERALL (mm)	INTERNAL (mm)	BASKET (mm)
40	340 x 185 x 380	240 x 137 x 150	195 x 105 x 80
90	400 x 295 x 380	300 x 240 x 150	240 x 190 x 80
120	400 x 295 x 380	300 x 240 x 200	240 x 190 x 130
300	600 x 350 x 430	500 x 300 x 200	450 x 250 x 130
400	640 x 425 x 510	500 x 300 x 300	450 x 250 x 260
500	620 x 465 x 525	500 x 400 x 300	450 x 350 x 260
800	770 x 565 x 505	600 x 500 x 300	560 x 450 x 260
SPECIFICATION			
MODEL	U/S POWER (W)	HEAT LOAD (W)	LIQUID CAPACITY (litres)
40	120	225	4
90	250	450	9
120	300	650	12
300	500	1200	28
400	750	1500	42
500	1000	1800	55
800	1250	2000	80