

BIO-CIRCLE™ HOT WASH

- Automated, Single-Stage Cleaning



The Hot Wash is a sturdy, automated, single-stage cleaning system for small parts.

The high-pressure spray system operating in conjunction with a powered, rotating, work basket provides thorough cleaning of a wide range of parts and contaminants, making the hot wash ideal for water-based parts cleaning in manufacturing, maintenance and service industries.

The Hot Wash is supplied complete with a high-performance, plate, oil separator that continuously removes contaminants from the wash solution, extending the lifetime of the cleaning system and reducing downtime.

The Hot Wash is ideally suited for use with the complementary range of 'STAR' biodegradable cleaning fluids.

MODEL:	HTW II—800	HTW II—1000	HTW II—1200
Material of Construction	Stainless Steel	Stainless Steel	Stainless Steel
Overall Dimensions (l x w x h) (mm)	900 x 1050 x 1050	1330 x 1280 x 1200	1530 x 1480 x 1400
Basket Diameter (mm)	800	1000	1200
Max. Clearance to Spray Bar (mm)	450	500	700
Maximum Payload (kgs)	100	250	350
Max. Operating Temperature (°C)	90	90	90
Heat Load (kW)	4.5	6	9
Tank Liquid Capacity (litres)	120	300	430

D&S Ultra-Clean Ltd
The Heath Business Park, Runcorn, Cheshire WA7 4QX.
Tel. 01928 580460 Fax. 01928 581058
www.ds-ultra.com